

※2系統

注1: 左給水専用です。
注2: 75, 100塩ビ管(VU, VP75・100)共用
塩ビ管の排水ソケットとの接合: 床上60±5mm

- * 給排水位置が適切でないと、止水栓が製品に干渉することがあります。
- * 製品背面に電源を設けないでください。
コンセントが製品と干渉し、抜き差しができない場合があります。
- * 電源コンセントは水や小水がかからない位置に設置してください。
また、壁給水の真下部に電源コンセントを設置したり、給水用ホースと電源コンセントを接触させないでください。感電・発火の原因になります。

別品番
(AC100Vリモコン)
リモコン取付用施工部材
・乾式・湿式工法壁用
・パーティション用

別途手配
電源電線：600Vビニル絶縁ビニルシースケーブル平形
VVF 2芯 $\phi 1.6$ 又は $\phi 2.0$

別品番
(タッチスイッチ)
リモコン取付用施工部材
・乾式・湿式工法壁用
・パーティション用

The technical drawing illustrates the R1/2 water supply unit in two views:

- Top View (平面図):** Shows the unit's footprint with a width of 300 mm. The inlet ports are positioned 100 mm from the top edge and 70 mm from the side edge, with a 30° angle indicated for the connection area. Labels point to the '上水側給水' (Main water supply) and '再生水側給水' (Recycled water supply) ports.
- Front View (正面図):** Shows the unit's profile and the '壁仕上面' (Wall finish top) and '床仕上面' (Floor finish top) levels. The R1/2 connection point is clearly marked.

床給水仕様の場合

Technical drawing of the front view of a vehicle, showing dimensions and callouts. The drawing includes a top-down view of the engine compartment with dimensions 120, 120, 100, 240, and 200~250. The main front view shows a hood with a height of 393, a grille with a height of 86, and a bumper with a height of 115. Callouts 注2 and 注3 are present.

Technical drawing of the TCM-1000 toilet, showing side and rear views with dimensions and connection details.

Side View Dimensions:

- Wall top (壁仕上面) to toilet front: 715 (Toilet front: 713)
- Flush valve connection: R1/2
- Water supply connection: $\phi 6.2 \times 63$ (Installation range: 190 ~ 210)
- Waste outlet connection: $\phi 6 \times 60$
- Waste outlet connection: $\phi 5.8 \times 56$
- Waste outlet connection: $\phi 6 \times 50$

Rear View Dimensions:

- Overall height: 608
- Height from floor to top of tank: 380
- Height from floor to top of bowl: 228
- Distance from wall to center of bowl: 300
- Distance from floor to top of bowl: 70
- Distance from floor to bottom of bowl: 150

Connection Details:

- Earth wire (アース線) L=200
- Power cord (電源コード) L=1000
- Water supply side (上水側給水)
- Recycled water side (再生水側給水)
- Wall water supply case (壁給水仕様の場合)

Manufacturer Information:

TCM

製図: 松本
検図:

TOTO			単位 mm	名称 ウォシュレット一体形 便器
製図 松本	検図 田添 二村 馨	日付 11-02-23	尺度 1 : 10	品番 CES952T17
備考 パブリック向け(音姫内蔵) 一般地・流動兼用、S排水		機能部: TCF952V17 ----- 陶器部: CS823B		